



# BALL VALVE DN15 PN40

Straight type - with direct mounting pad - fire safe

20-00000966  
445194

**DESCRIPTION:** Two piece, full bore, Stainless Steel body ball valve with Stainless Steel ball and SS+PTFE seat. Raised face flanges. With direct mounting pad. Fire safe version.

**STANDARD & DESIGN:**

End Standard	DIN 2635
Face To Face Standard	EN 558, series 14
Inspection Standard	EN 12266
Remark	Connection: PN40
Top Flange Standard	ISO 5211 - F04
Throughput Direction	Straight
Execution	Full Bore
Variant	Fire Safe
End Type	Flanged
Design Code	ASME B16.34
Standard	DIN
Material Seat	SS+PTFE
Material Body	Stainless Steel, 316
Sub Category	BALL
Item Number	20-00000966
Category	Valve



No	Part	Material	Code	Application
1	Body	Stainless Steel	ASTM A351-CF8M	Air
2	Cap	Stainless Steel	ASTM A351-CF8M	Boiler feedwater
3	Ball	Stainless Steel	ASTM A351-CF8M	Cargo oil
4	Seat	SS+PTFE		Condensate
5	Stem	Stainless Steel	AISI 316	Corrosive fluids
6	Handle	Stainless Steel, Plastic Cover	AISI 430	Flammable hydraulic oil
				Fuel oil
				Gas
				Lubricating oil
				Non-flammable hydraulic fluid
				Sea water
				Water

DN	Pressure Rating Id	nxdd	Hcd	Ø D	L	Kg	L1	H	H1	H2	S
15	40	4x14	65	95	115	2.2	110	89	46.5	56	9

