



BALL VALVE 3/4" 1200WOG

Straight type

20-00000995
440095

DESCRIPTION: Three piece, full bore, Stainless Steel body ball valve with Stainless Steel ball and PTFE seat. Standardized pattern for actuator mounting. Female threaded ends.

STANDARD & DESIGN:

| | |
|----------------------|---------------------------|
| End Standard | ISO 228-1 |
| Top Flange Standard | ISO 5211 - F03 non-direct |
| Throughput Direction | Straight |
| Execution | Full Bore |
| End Type | Threaded |
| Standard | DIN |
| Material Seat | CPTFE |
| Material Body | Stainless Steel, 316 |
| Sub Category | BALL |
| Item Number | 20-00000995 |
| Category | Valve |



| No | Part | Material | Code | Application |
|----|--------|--------------------------------|----------------|-------------------------------|
| 1 | Body | Stainless Steel | ASTM A351-CF8M | Air |
| 2 | Cap | Stainless Steel | ASTM A351-CF8M | Boiler feedwater |
| 3 | Ball | Stainless Steel | ASTM A351-CF8M | Cargo oil |
| 4 | Seat | CPTFE | | Condensate |
| 5 | Stem | Stainless Steel | AISI 316 | Corrosive fluids |
| 6 | Handle | Stainless Steel, Plastic Cover | AISI 430 | Flammable hydraulic oil |
| | | | | Fuel oil |
| | | | | Gas |
| | | | | Lubricating oil |
| | | | | Non-flammable hydraulic fluid |
| | | | | Sea water |
| | | | | Water |

| DN | Pressure Rating Id | L | Kg | L1 | Inch | H | Ø A |
|----|--------------------|----|-----|-----|------|----|-----|
| 20 | 1200 | 76 | 0.7 | 110 | 3/4" | 63 | 20 |

