



BUTTERFLY VALVE L DN350 PN10

M34169
710701

Lug type - with gearbox

DESCRIPTION: Nodular Cast Iron body, vulcanized liner lugged type butterfly valve with Aluminium Bronze disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

STANDARD & DESIGN:

End Standard	EN 1092-2
Face To Face Standard	EN 558, series 20
Inspection Standard	EN 12266
Remark	Connection: PN10
Min temperature	-15°C
Top Flange Standard	ISO 5211 - F12
Max temperature	+80°C
Variant	Gearbox
End Type	Lug
Design Code	EN 593
Standard	DIN
Material Seat	NBR
Material Disc	Aluminium Bronze
Material Body	Nodular Cast Iron, GGG40
Sub Category	BUTTERFLY
Item Number	M34169
Category	Valve



No	Part	Material	Code	Application
1	Body	Nodular Cast Iron	GGG40	Air
2	Disc	Aluminium Bronze		Boiler feedwater
3	Seat	NBR max working temp. 80°C		Cargo oil
4	Stem	Stainless Steel	1.4057	Condensate
5	Pin	Duplex Stainless Steel	1.4462	Flammable hydraulic oil
6	Gearbox	Cast Iron	GG20	Fuel oil
7	Gearbox shaft	Steel	C45	Gas
				Lubricating oil
				Non-flammable hydraulic fluid
				Sea water
				Water

DN	Pressure Rating Id	nxdd	Hcd	Ø D	L	Kg	L1	H	H1	L2	H2	Ø M
350	10	16xM20	460	516	78	65	210	675	288	66	315	300

