



BUTTERFLY VALVE L DN500 PN10

M34202
710901

Lug type - with gearbox

DESCRIPTION: Nodular Cast Iron body, vulcanized liner lugged type butterfly valve with Stainless Steel disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

STANDARD & DESIGN:

End Standard	EN 1092-2
Face To Face Standard	EN 558, series 20
Inspection Standard	EN 12266
Remark	Connection: PN10
Min temperature	-15°C
Top Flange Standard	ISO 5211 - F14
Max temperature	+80°C
Variant	Gearbox
End Type	Lug
Design Code	EN 593
Standard	DIN
Material Seat	NBR
Material Disc	Stainless Steel, 316
Material Body	Nodular Cast Iron, GGG40
Sub Category	BUTTERFLY
Item Number	M34202
Category	Valve



No	Part	Material	Code	Application
5	Pin	Duplex Stainless Steel	1.4462	Air
6	Gearbox	Cast Iron	GG20	Boiler feedwater
7	Gearbox shaft	Steel	C45	Cargo oil
1	Body	Nodular Cast Iron	GGG40	Condensate
2	Disc	Stainless Steel	1.4408	Flammable hydraulic oil
3	Seat	NBR max working temp. 80°C		Fuel oil
4	Stem	Stainless Steel	1.4057	Gas
				Lubricating oil
				Non-flammable hydraulic fluid
				Sea water
				Water

DN	Pressure Rating Id	nxdd	Hcd	Ø D	L	Kg	L1	H	H1	L2	H2	Ø M
500	10	20xM24	620	710	127	184	357	885	379	123	415	500

