



BUTTERFLY VALVE DF DN40 PN16

M34687
730902

Double flange type - bare stem

DESCRIPTION: Nodular Cast Iron body, vulcanized liner double flange type butterfly valve with Stainless Steel disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous

STANDARD & DESIGN:

| | |
|-----------------------|--------------------------|
| End Standard | EN 1092-2 |
| Face To Face Standard | EN 558, series 13 |
| Inspection Standard | EN 12266 |
| Remark | Connection: PN16 |
| Min temperature | -15°C |
| PartNumberListId | 0 |
| Top Flange Standard | ISO 5211 - F07 |
| Max temperature | +80°C |
| Variant | Bare stem |
| End Type | Double flange |
| Design Code | EN 593 |
| Standard | DIN |
| Material Seat | NBR |
| Material Disc | Stainless Steel, 316 |
| Material Body | Nodular Cast Iron, GGG40 |
| Sub Category | BUTTERFLY |
| Item Number | M34687 |
| Category | Valve |



| No | Part | Material | Code | Application |
|----|------|----------------------------|--------|-------------------------------|
| 1 | Body | Nodular Cast Iron | GGG40 | Air |
| 2 | Disc | Stainless Steel | 1.4408 | Boiler feedwater |
| 3 | Seat | NBR max working temp. 80°C | | Cargo oil |
| 4 | Stem | Stainless Steel | 1.4401 | Condensate |
| 5 | Pin | Duplex Stainless Steel | 1.4462 | Flammable hydraulic oil |
| | | | | Fuel oil |
| | | | | Gas |
| | | | | Lubricating oil |
| | | | | Non-flammable hydraulic fluid |
| | | | | Sea water |
| | | | | Water |

| DN | Pressure Rating Id | nxdd | Hcd | Ø D | L | Kg | Ø D2 | H2 | S | H3 |
|----|--------------------|------|-----|-----|-----|-----|------|-----|----|----|
| 40 | 16 | 4x18 | 110 | 150 | 106 | 5.5 | 90 | 113 | 11 | 19 |

