



# BUTTERFLY VALVE DF DN50 PN16

M34688  
730902

Double flange type - bare stem

**DESCRIPTION:** Nodular Cast Iron body, vulcanized liner double flange type butterfly valve with Stainless Steel disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous

**STANDARD & DESIGN:**

End Standard	EN 1092-2
Face To Face Standard	EN 558, series 13
Inspection Standard	EN 12266
Remark	Connection: PN16
Min temperature	-15°C
PartNumberListId	0
Top Flange Standard	ISO 5211 - F07
Max temperature	+80°C
Variant	Bare stem
End Type	Double flange
Design Code	EN 593
Standard	DIN
Material Seat	NBR
Material Disc	Stainless Steel, 316
Material Body	Nodular Cast Iron, GGG40
Sub Category	BUTTERFLY
Item Number	M34688
Category	Valve



No	Part	Material	Code	Application
2	Disc	Stainless Steel	1.4408	Air
3	Seat	NBR max working temp. 80°C		Boiler feedwater
4	Stem	Stainless Steel	1.4401	Cargo oil
5	Pin	Duplex Stainless Steel	1.4462	Condensate
1	Body	Nodular Cast Iron	GGG40	Flammable hydraulic oil
				Fuel oil
				Gas
				Lubricating oil
				Non-flammable hydraulic fluid
				Sea water
				Water

DN	Pressure Rating Id	nxdd	Hcd	Ø D	L	Kg	H1	Ø D2	H2	S	H3
50	16	4x18	125	165	108	6.7	71	90	118	11	19

