



BUTTERFLY VALVE W DN300 PN10

M34821
700701

Wafer type - with gearbox

DESCRIPTION: Nodular Cast Iron body, vulcanized liner wafer type butterfly valve with Aluminium Bronze disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

STANDARD & DESIGN:

| | |
|-----------------------|---|
| End Standard | EN 1092-2 |
| Face To Face Standard | EN 558, series 20 |
| Inspection Standard | EN 12266 |
| Remark | Multiflange: PN6/10/16/25, ANSI150, JIS5K/10K |
| Min temperature | -15°C |
| Top Flange Standard | ISO 5211 - F10 |
| Max temperature | +80°C |
| Variant | Gearbox |
| End Type | Wafer |
| Design Code | EN 593 |
| Standard | DIN |
| Material Seat | NBR |
| Material Disc | Aluminium Bronze |
| Material Body | Nodular Cast Iron, GGG40 |
| Sub Category | BUTTERFLY |
| Item Number | M34821 |
| Category | Valve |



| No | Part | Material | Code | Application |
|----|---------------|----------------------------|--------|-------------------------------|
| 1 | Body | Nodular Cast Iron | GGG40 | Air |
| 2 | Disc | Aluminium Bronze | | Boiler feedwater |
| 3 | Seat | NBR max working temp. 80°C | | Cargo oil |
| 4 | Stem | Stainless Steel | 1.4401 | Condensate |
| 5 | Pin | Duplex Stainless Steel | 1.4462 | Flammable hydraulic oil |
| 6 | Gearbox | Cast Iron | GG20 | Fuel oil |
| 7 | Gearbox shaft | Steel | C45 | Gas |
| | | | | Lubricating oil |
| | | | | Non-flammable hydraulic fluid |
| | | | | Sea water |
| | | | | Water |

| DN | Pressure Rating Id | Ø D | L | Kg | L1 | H | H1 | L2 | H2 | Ø M |
|-----|--------------------|-----|----|----|-----|-----|-----|----|-----|-----|
| 300 | 10 | 373 | 78 | 42 | 210 | 582 | 240 | 66 | 270 | 300 |

