



BUTTERFLY VALVE W DN250 PN10

M34826
702901

Wafer type - with gearbox

DESCRIPTION: Nodular Cast Iron body, vulcanized liner wafer type butterfly valve with Stainless Steel disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

STANDARD & DESIGN:

End Standard	EN 1092-2
Face To Face Standard	EN 558, series 20
Inspection Standard	EN 12266
Remark	Multiflange: PN10/16/25, ANSI150, JIS5K/10K
Min temperature	-30°C
Top Flange Standard	ISO 5211 - F10
Max temperature	+180°C
Variant	Gearbox
End Type	Wafer
Design Code	EN 593
Standard	DIN
Material Seat	FPM/FKM
Material Disc	Stainless Steel, 316
Material Body	Nodular Cast Iron, GGG40
Sub Category	BUTTERFLY
Item Number	M34826
Category	Valve



No	Part	Material	Code	Application
1	Body	Nodular Cast Iron	GGG40	Cargo oil
2	Disc	Stainless Steel	1.4408	Corrosive fluids
3	Seat	FPM/FKM max working temp. 180°C		Flammable hydraulic oil
4	Stem	Stainless Steel	1.4401	Fuel oil
5	Pin	Duplex Stainless Steel	1.4462	Lubricating oil
6	Gearbox	Cast Iron	GG20	Non-flammable hydraulic fluid
7	Gearbox shaft	Steel	C45	

DN	Pressure Rating Id	Ø D	L	Kg	L1	H	H1	L2	H2	Ø M
250	10	318	68	33	210	519	202	66	245	300

