



# BUTTERFLY VALVE DF DN400 PN10

Double flange type - bare stem

M35154  
731801

**DESCRIPTION:** Nodular Cast Iron body, vulcanized liner double flange type butterfly valve with Super Duplex disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

**STANDARD & DESIGN:**

End Standard	EN 1092-2
Face To Face Standard	EN 558, series 13
Inspection Standard	EN 12266
Remark	Connection: PN10
Min temperature	-20°C
Top Flange Standard	ISO 5211 - F12
Max temperature	+100°C
Variant	Bare stem
End Type	Double flange
Design Code	EN 593
Standard	DIN
Material Seat	EPDM
Material Disc	Stainless Steel, Super Duplex
Material Body	Nodular Cast Iron, GGG40
Sub Category	BUTTERFLY
Item Number	M35154
Category	Valve



No	Part	Material	Code	Application
1	Body	Nodular Cast Iron	GGG40	Boiler feedwater
2	Disc	Super Duplex Stainless Steel	1.4469	Condensate
3	Seat	EPDM max working temp. 100°C		Sea water
4	Stem	Stainless Steel	1.4057	Water
5	Pin	Duplex Stainless Steel	1.4462	

DN	Pressure Rating Id	nxdd	Hcd	Ø D	L	Kg	H1	Ø D2	H2	S	H3
400	10	16x28	515	565	216	101	305	150	350	27	30

