



BUTTERFLY VALVE DF DN150 JIS 5K

Double flange type - bare stem

M35422
732701

DESCRIPTION: Nodular Cast Iron body, vulcanized liner double flange type butterfly valve with Aluminium Bronze disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous

STANDARD & DESIGN:

End Standard	JIS B2239
Face To Face Standard	EN 558, series 13
Inspection Standard	EN 12266
Remark	Connection: JIS 5K
Min temperature	-30°C
PartNumberListId	0
Top Flange Standard	ISO 5211 - F07
Max temperature	+180°C
Variant	Bare stem
End Type	Double flange
Design Code	EN 593
Standard	JIS
Material Seat	FPM/FKM
Material Disc	Aluminium Bronze
Material Body	Nodular Cast Iron, GGG40
Sub Category	BUTTERFLY
Item Number	M35422
Category	Valve



No	Part	Material	Code	Application
1	Body	Nodular Cast Iron	GGG40	Cargo oil
2	Disc	Aluminium Bronze		Corrosive fluids
3	Seat	FPM/FKM max working temp. 180°C		Flammable hydraulic oil
4	Stem	Stainless Steel	1.4401	Fuel oil
5	Pin	Duplex Stainless Steel	1.4462	Lubricating oil
				Non-flammable hydraulic fluid

DN	Pressure Rating Id	nxdd	Hcd	Ø D	L	Kg	H1	Ø D2	H2	S	H3
150	5	8x19	230	285	140	18	140	90	180	14	20

