



BUTTERFLY VALVE L DN80 JIS 5K

Lug type - with lever

M35537
712701

DESCRIPTION: Nodular Cast Iron body, vulcanized liner lugged type butterfly valve with Aluminium Bronze disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

STANDARD & DESIGN:

End Standard	JIS B2239
Face To Face Standard	EN 558, series 20
Inspection Standard	EN 12266
Remark	Connection: JIS 5K
Min temperature	-30°C
Top Flange Standard	ISO 5211 - F07
Max temperature	+180°C
Variant	Lever
End Type	Lug
Design Code	EN 593
Standard	JIS
Material Seat	FPM/FKM
Material Disc	Aluminium Bronze
Material Body	Nodular Cast Iron, GGG40
Sub Category	BUTTERFLY
Item Number	M35537
Category	Valve



No	Part	Material	Code	Application
2	Disc	Aluminium Bronze		Cargo oil
3	Seat	FPM/FKM max working temp. 180°C		Corrosive fluids
4	Stem	Stainless Steel	1.4401	Flammable hydraulic oil
5	Pin	Duplex Stainless Steel	1.4462	Fuel oil
6	Lever	Nodular Cast Iron	GGG40	Lubricating oil
7	Position plate	Stainless Steel	1.4401	Non-flammable hydraulic fluid
1	Body	Nodular Cast Iron	GGG40	

DN	Pressure Rating Id	nxdd	Hcd	Ø D	L	Kg	L1	H	H1	L2	H2
80	5	4xM16	145	188	46	6.2	232	274,5	88	101	133

