



BUTTERFLY VALVE L DN700 PN6

Lug type - with gearbox

M36295
712700

DESCRIPTION: Nodular Cast Iron body, vulcanized liner lugged type butterfly valve with Aluminium Bronze disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

STANDARD & DESIGN:

| | |
|-----------------------|--------------------------|
| End Standard | EN 1092-2 |
| Face To Face Standard | EN 558, series 20 |
| Inspection Standard | EN 12266 |
| Remark | Connection: PN6 |
| Min temperature | -30°C |
| Top Flange Standard | ISO 5211 - F16 |
| Max temperature | +180°C |
| Variant | Gearbox |
| End Type | Lug |
| Design Code | EN 593 |
| Standard | DIN |
| Material Seat | FPM/FKM |
| Material Disc | Aluminium Bronze |
| Material Body | Nodular Cast Iron, GGG40 |
| Sub Category | BUTTERFLY |
| Item Number | M36295 |
| Category | Valve |



| No | Part | Material | Code | Application |
|----|---------------|---------------------------------|--------|-------------------------------|
| 1 | Body | Nodular Cast Iron | GGG40 | Cargo oil |
| 2 | Disc | Aluminium Bronze | | Corrosive fluids |
| 3 | Seat | FPM/FKM max working temp. 180°C | | Flammable hydraulic oil |
| 4 | Stem | Stainless Steel | 1.4057 | Fuel oil |
| 5 | Pin | Duplex Stainless Steel | 1.4462 | Lubricating oil |
| 6 | Gearbox | Cast Iron | GG25 | Non-flammable hydraulic fluid |
| 7 | Gearbox shaft | Steel | C45 | |

| DN | Pressure Rating Id | nxdd | Hcd | Ø D | L | Kg | L1 | H | H1 | L2 | H2 | Ø M |
|-----|--------------------|--------|-----|-----|-----|-----|-----|------|-----|----|-----|-----|
| 700 | 6 | 24xM24 | 810 | 900 | 165 | 321 | 344 | 1166 | 485 | 53 | 555 | 500 |

