



DUAL PLATE CHECK VALVE DN80 PN16

Wafer type

M33633
302702

DESCRIPTION: Nodular Cast Iron body, vulcanized injection molded FPM/FKM liner dual plate check valve with Aluminium Bronze disc. Opening pressure less than 0,2 bar.

STANDARD & DESIGN:

Face To Face Standard
Remark

Min temperature
Max temperature
Throughput Direction
End Type
Standard
Material Seat
Material Disc
Material Body
Sub Category
Item Number
Category

EN 558, series 16
Multiflange: PN6/10/16,
ANSI150, JIS5K/10K
-30°C
+180°C
Straight
Wafer
DIN
FPM/FKM
Aluminium Bronze
Nodular Cast Iron, GGG40
CHECK
M33633
Valve



No	Part	Material	Code	Application
3	Disc	Aluminium Bronze		Cargo oil
4	Spring	Inconel		Corrosive fluids
5	Shaft	Monel		Flammable hydraulic oil
6	Clips	Aluminium Bronze		Fuel oil
1	Body	Nodular Cast Iron	GGG40	Lubricating oil
2	Seat	FPM/FKM		Non-flammable hydraulic fluid

DN	Pressure Rating Id	Ø D	L	Kg	L1	Ø D1
80	16	128	64	3.8	11	63

