



# DUAL PLATE CHECK VALVE DN250 PN16

Wafer type

M33638  
302702

**DESCRIPTION:** Nodular Cast Iron body, vulcanized injection molded FPM/FKM liner dual plate check valve with Aluminium Bronze disc. Opening pressure less than 0,2 bar.

**STANDARD & DESIGN:**

Face To Face Standard  
Remark

Min temperature  
Max temperature  
Throughput Direction  
End Type  
Standard  
Material Seat  
Material Disc  
Material Body  
Sub Category  
Item Number  
Category

EN 558, series 16  
Multiflange: PN6/10/16,  
ANSI150, JIS5K/10K  
-30°C  
+180°C  
Straight  
Wafer  
DIN  
FPM/FKM  
Aluminium Bronze  
Nodular Cast Iron, GGG40  
CHECK  
M33638  
Valve



No	Part	Material	Code	Application
1	Body	Nodular Cast Iron	GGG40	Cargo oil
2	Seat	FPM/FKM		Corrosive fluids
3	Disc	Aluminium Bronze		Flammable hydraulic oil
4	Spring	Inconel		Fuel oil
5	Shaft	Monel		Lubricating oil
6	Clips	Aluminium Bronze		Non-flammable hydraulic fluid

DN	Pressure Rating Id	Ø D	L	Kg	L1	Ø D1
250	16	306	114	26	78	203

