



# DUAL PLATE CHECK VALVE DN600 PN10

Wafer type

M33644  
302701

**DESCRIPTION:** Nodular Cast Iron body, vulcanized injection molded FPM/FKM liner dual plate check valve with Aluminium Bronze disc. Opening pressure less than 0,2 bar.

**STANDARD & DESIGN:**

Face To Face Standard  
Remark

EN 558, series 16  
Multiflange: PN6/10/16,  
ANSI150, JIS5K/10K  
-30°C  
+180°C  
Straight  
Wafer  
DIN  
FPM/FKM  
Aluminium Bronze  
Nodular Cast Iron, GGG40  
CHECK  
M33644  
Valve

Min temperature  
Max temperature  
Throughput Direction  
End Type  
Standard  
Material Seat  
Material Disc  
Material Body  
Sub Category  
Item Number  
Category



No	Part	Material	Code	Application
1	Body	Nodular Cast Iron	GGG40	Cargo oil
2	Seat	FPM/FKM		Corrosive fluids
3	Disc	Aluminium Bronze		Flammable hydraulic oil
4	Spring	Inconel		Fuel oil
5	Shaft	Monel		Lubricating oil
6	Clips	Aluminium Bronze		Non-flammable hydraulic fluid

DN	Pressure Rating Id	Ø D	L	Kg	L1	Ø D1
600	10	670	222	200	170	545

