



SWING CHECK VALVE DN65 PN10

M40200
370202

DESCRIPTION: Nodular Cast Iron body, full bore swing check valve with NBR soft sealing. Raised face flanges.

STANDARD & DESIGN:

| | |
|-----------------------|----------------------------|
| End Standard | EN 1092-2 |
| Face To Face Standard | EN 558, series 48 |
| Remark | Connection: PN16 |
| Min temperature | -10°C |
| Max temperature | +120°C |
| Throughput Direction | Straight |
| Execution | Full Bore |
| End Type | Flanged |
| Design Code | DIN 3232 |
| Standard | DIN |
| Material Seat | NBR |
| Material Disc | Stainless Steel, 304 |
| Material Body | Nodular Cast Iron, GGG40.3 |
| Sub Category | CHECK |
| Item Number | M40200 |
| Category | Valve |



| No | Part | Material | Code | Application |
|----|---------------|-------------------|---------|-------------------------------|
| 1 | Body | Nodular Cast Iron | GGG40.3 | Boiler feedwater |
| 2 | Bonnet | Nodular Cast Iron | GGG40.3 | Cargo oil |
| 3 | Body seat | Stainless Steel | 1.4301 | Condensate |
| 4 | Disc | Nodular Cast Iron | GGG40.3 | Flammable hydraulic oil |
| 5 | Disc sealing | NBR | | Fuel oil |
| 6 | Stem | Brass | CW 614N | Lubricating oil |
| 7 | Hinge arm | Nodular Cast Iron | GGG40.3 | Non-flammable hydraulic fluid |
| 8 | Bonnet gasket | Asbestos Free | | Sea water |
| | | | | Steam |
| | | | | Water |

| DN | Pressure Rating Id | nxdd | Hcd | Ø D | L | Kg | H |
|----|--------------------|------|-----|-----|-----|----|-----|
| 65 | 16 | 4x18 | 145 | 185 | 240 | 15 | 120 |

