



GLOBE VALVE DN65 PN16

Angled type - SDSL

M61513
467102

DESCRIPTION: Angled type, Nodular Cast Iron body, metal seated globe valve with rising stem and bolted bonnet. Raised face flanges.

STANDARD & DESIGN:

| | |
|-----------------------|--------------------------|
| End Standard | EN 1092-2 |
| Face To Face Standard | EN 558, series 8 |
| Inspection Standard | EN 12266 |
| Remark | Connection: PN16 |
| Throughput Direction | Angled |
| Variant | SDSL |
| End Type | Flanged |
| Design Code | EN 13789 |
| Standard | DIN |
| Material Seat | Bronze |
| Material Disc | Bronze |
| Material Body | Nodular Cast Iron, GGG40 |
| Sub Category | GLOBE |
| Item Number | M61513 |
| Category | Valve |



| No | Part | Material | Code | Application |
|----|---------------|-------------------|-------|-------------------------------|
| 1 | Body | Nodular Cast Iron | GGG40 | Boiler feedwater |
| 2 | Bonnet | Nodular Cast Iron | GGG40 | Cargo oil |
| 3 | Seat | Bronze | RG5 | Condensate |
| 4 | Disc | Bronze | RG5 | Flammable hydraulic oil |
| 5 | Stem | Special Brass | Som59 | Flammable media |
| 6 | Gland packing | Graphite | | Fuel oil |
| 7 | Gasket | Graphite | | Lubricating oil |
| 8 | Handwheel | Cast Iron | GG25 | Non-flammable hydraulic fluid |
| | | | | Sea water |
| | | | | Water |

| DN | Pressure Rating Id | nxdd | Hcd | Ø D | L | Kg | H | Ø M |
|----|--------------------|------|-----|-----|-----|----|-----|-----|
| 65 | 16 | 4x19 | 145 | 185 | 145 | 16 | 246 | 140 |

