



SELF CLOSING VALVE DN65 PN16

M75668
921002

with lever and handwheel

DESCRIPTION: Straight type, Nodular Cast Iron, metal seated, self closing globe valve. Bolted bonnet and automatic spring closing. Can be locked in closed position by the handwheel. Raised face flanges.

STANDARD & DESIGN:

End Standard	ISO 7005-2
Face To Face Standard	ISO 5752, series 1
Inspection Standard	EN 12266
Remark	Connection: PN16
Throughput Direction	Straight
End Type	Flanged
Standard	DIN
Material Seat	Stainless Steel, 304
Material Disc	Stainless Steel, 304
Material Body	Nodular Cast Iron, GGG40
Sub Category	SELF
Item Number	M75668
Category	Valve



No	Part	Material	Code	Application
4	Spring	Spring Steel	1084 ASTM A713	Boiler feedwater
5	Gasket	NBR bonded aramid		Cargo oil
6	Bonnet	Nodular Cast Iron	GGG40	Condensate
7	O-ring	FPM/FKM		Flammable hydraulic oil
8	Setting nut	Brass	CW 617N	Fuel oil
9	Stem	Stainless Steel	1.4301	Lubricating oil
10	Handwheel	Cast Iron	GG25	Non-flammable hydraulic fluid
11	Lever	Stainless Steel	1.4301	Sea water
1	Body	Nodular Cast Iron	GGG40	Thermal oil
2	Seat ring	Stainless Steel	1.4301	Water
3	Disc	Stainless Steel	1.4301	

DN	Pressure Rating Id	nxdd	Hcd	Ø D	L	Kg	L1	H	Ø M
65	16	4x19	145	185	290	17	278	254	140

