



STORM VALVE DN150 PN4/PN10

Straight type

M36500
159801

DESCRIPTION: Straight type closable check valve. Nodular Cast Iron body. Soft sealing disc. Flat face flanges.

STANDARD & DESIGN:

| | |
|-----------------------|--------------------------|
| End Standard | EN 1092-2 |
| Face To Face Standard | EN 558, series 48 |
| Inspection Standard | EN 12266 |
| Remark | Connection: PN 10 |
| Throughput Direction | Straight |
| End Type | Flanged |
| Standard | DIN |
| Material Seat | NBR |
| Material Disc | Nodular Cast Iron, GGG40 |
| Material Body | Nodular Cast Iron, GGG40 |
| Sub Category | STORM |
| Item Number | M36500 |
| Category | Valve |



| No | Part | Material | Code | Application |
|----|--------------|-------------------|---------|-------------|
| 9 | Plug | Zinc Plated Steel | | Sea water |
| 1 | Body | Nodular Cast Iron | GGG40 | Water |
| 2 | Disc | Nodular Cast Iron | GGG40 | |
| 3 | Disc sealing | NBR | | |
| 4 | Sleeve | Brass | CW 614N | |
| 5 | Sealing | NBR | | |
| 6 | Stem | Brass | CW 614N | |
| 7 | Shaft | Brass | CW 614N | |
| 8 | Spring | Stainless Steel | 1.4310 | |

| DN | Pressure Rating Id | nxdd | Hcd | Ø D | L | Kg | H | H1 | Ø M |
|-----|--------------------|------|-----|-----|-----|------|-----|-----|-----|
| 150 | 4 | 8x23 | 240 | 285 | 304 | 35.1 | 530 | 400 | 140 |

