



STORM VALVE DN125 PN4/PN10

Angled type

M36505
159301

DESCRIPTION: Angled type closable check valve. Nodular Cast Iron body. Soft sealing disc. Flat face flanges. Different inlet/outlet diameter.

STANDARD & DESIGN:

| | |
|-----------------------|--------------------------|
| End Standard | EN 1092-2 |
| Face To Face Standard | DIN HNA Sr 6 |
| Inspection Standard | EN 12266 |
| Remark | Connection: PN10 |
| Throughput Direction | Angled |
| End Type | Flanged |
| Standard | DIN |
| Material Seat | NBR |
| Material Disc | Nodular Cast Iron, GGG40 |
| Material Body | Nodular Cast Iron, GGG40 |
| Sub Category | STORM |
| Item Number | M36505 |
| Category | Valve |



| No | Part | Material | Code | Application |
|----|--------------|-------------------|---------|-------------|
| 1 | Body | Nodular Cast Iron | GGG40 | Sea water |
| 2 | Disc | Nodular Cast Iron | GGG40 | Water |
| 3 | Disc sealing | NBR | | |
| 4 | Sleeve | Brass | CW 614N | |
| 5 | Sealing | NBR | | |
| 6 | Stem | Brass | CW 614N | |
| 7 | Shaft | Brass | CW 614N | |
| 8 | Spring | Stainless Steel | 1.4310 | |
| 9 | Plug | Zinc Plated Steel | | |

| DN | Pressure Rating Id | Ø D | L | Kg | H | H1 | n1xØd1 | Hcd1 | Ø D1 | n2xØd2 | Ø D2 | Ø M | Hcd2 |
|-----|--------------------|-----|-----|------|-----|-----|--------|------|------|--------|------|-----|------|
| 125 | 4 | 158 | 290 | 29.3 | 322 | 152 | 8x19 | 210 | 250 | 8x23 | 315 | 140 | 270 |

